

Webbing sling,
duplex construction,
steel links on both ends
model HBD-SN and
model HBD-SD

Made from polyester (PES), EN 1492-1 form Cr2,
with capacity label.

Features

- Duplex construction, PU-starched, thermally fixed.
- With steel D- and DP-links (reevable).
- Woven tonnage stripes.
- Low weight allows easy handling.
- Protection against hand injuries.
- Protection against cargo surface damage.
- Consistent pressure distribution onto pressure- and pull sensitive loads.
- UV-resistant, eliminating material ageing or embrittlement.
- Heat resistant up to +100° C.
- Moisture-resistant fabric, thus preventing frost damage (up to approx. -40° C).
- Low elongation (< 4%).



Model HBD-SD - links are reevable, webbing sling also applicable for use in choke hitch.

Technical data model HBD-SN and model HBD-SD

Model	Colour code EN 1492	Capacity WLL, with one sling, straight pull kg	Capacity WLL, with one sling, basket, angle β up to 7° kg	Capacity WLL, with one sling, basket, angle β 7°- 45° kg	Capacity WLL, with one sling, basket, angle β 45°- 60° kg	Capacity WLL, with one sling, choke hitch kg	Webbing width mm	Link dimension HBD-SN bxdxt mm	Link dimension HBD-SD bxdxt mm
HBD-01000	violet	1000	2000	1400	1000	800	50	50x13x95	50x13x145
HBD-02000	green	2000	4000	2800	2000	1600	60	60x16x90	60x16x165
HBD-03000	yellow	3000	6000	4200	3000	2400	90	90x18x110	90x18x190
HBD-04000	grey	4000	8000	5600	4000	3200	120	120x22x130	120x22x240
HBD-05000	red	5000	10000	7000	5000	4000	150	150x26x170	150x26x300
HBD-06000	brown	6000	12000	8400	6000	4800	180	180x30x200	180x30x320
HBD-08000	blue	8000	16000	11200	8000	6400	240	240x32x230	240x32x360
HBD-10000	orange	10000	20000	14000	10000	8000	300	300x40x290	300x40x435